

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A jewelry storage system for storing and allowing access to and removal of jewelry pieces, comprising:

a jewelry cabinet defining an interior space, the jewelry cabinet comprising:

a ~~box~~ frame including a top wall, bottom wall, two sidewalls and a back wall, at least one of the two sidewalls including an opening;

a door connected to the ~~box~~ frame wherein the door extends substantially from the top wall to the bottom wall; and

a plurality of jewelry storage elements attached within the interior space; ~~and~~

a stand configured to receive the jewelry cabinet to hold the jewelry cabinet in an upright position so that the back wall of the jewelry cabinet forms an angle α from the horizontal; and

a peg adapted to be placed in the opening in the cabinet sidewall such that the peg extends from the sidewall to rest against an outer surface of the stand and thereby hold the cabinet at the angle α being less than approximately 90 degrees.

2. (Original) The jewelry storage system according to claim 1, further comprising a mirror attached to an exterior surface of the door.

3. – 5. Canceled

6. (Currently amended) The jewelry storage system according to claim 1, wherein the plurality of jewelry storage elements includes a bracelet bar and a plurality of shelves attached to one of an interior surface of the ~~box~~ frame and the door.

7. (Original) The jewelry storage system according to claim 1, wherein at least one of the plurality of jewelry storage elements is capable of being relocated within the jewelry cabinet.

8.(Original) The jewelry storage system according to claim 6, wherein the bracelet bar is removably attached to the interior surface of the door, the bracelet bar being configured such that it can be moved and relocated to other locations on an interior surface of the door.

9.(Original) The jewelry storage system according to claim 8, wherein the bracelet bar is removably attached to the interior surface of the door by at least one magnet.

10.(Original) The jewelry storage system according to claim 6, wherein the plurality of shelves include at least one front wall member, the front wall member extending upward from a front surface of the shelves.

11.(Original) The jewelry storage system according to claim 10, wherein the plurality of shelves further include movable dividers that divide a top surface of the shelves.

12.(Currently amended) The jewelry storage system according to claim 1, wherein the plurality of jewelry storage elements include a hook bar, the hook bar having a plurality of hooks and being attached to at least one of an interior surface of the door and the box frame.

13.(Original) The jewelry storage system according to claim 12, wherein the plurality of jewelry storage elements further include a pouch, wherein the pouch is located beneath the hook bar and is configured to capture lengthy pieces of jewelry placed on the plurality of hooks.

14.(Currently amended) The jewelry storage system according to claim 1, wherein the plurality of jewelry storage elements include an earring bar, the earring bar having a plurality of openings and being attached to at least one of an interior surface of the door and the box frame.

15.(Withdrawn) The jewelry storage system according to claim 1, further comprising a mounting structure on an outer side of the back wall of the box frame configured to permit hanging the jewelry cabinet on a vertical surface.

16.(Withdrawn) The jewelry storage system according to claim 1, wherein the stand includes at least one drawer.

17.(Currently amended) A ~~mirrored~~ jewelry storage system for storing and allowing access to and removal of jewelry pieces, comprising:

a jewelry cabinet defining an interior space, the jewelry cabinet comprising:

a frame including a top, bottom wall, two sides and a back wall;

a door connected to the frame; and

a plurality of jewelry storage elements attached within the interior space; ~~and~~

~~a mirror on an exterior surface of the door; and~~

a stand configured to receive the jewelry cabinet so that the back wall of the jewelry cabinet forms an angle α from the horizontal, the stand including an inside surface adjacent one of the two sides of the frame and a peg extending from the inside surface of the stand to contact an outside surface of the frame wherein the jewelry cabinet may be pivoted with respect to the stand to move between a first position useful for accessing the interior space where the angle α is about 90 degrees and a second position useful for using the mirror where the angle α is less than 90 degrees.

18. (Currently amended) The jewelry storage system according to claim 17, ~~further comprising an angle adjusting element, the angle adjusting element configured to determine the angle α of the jewelry cabinet, with~~ wherein the jewelry cabinet may be pivoted with respect to the stand to vary the angle α being between from about 60 degrees and to about 90 degrees.

19. (Currently amended) The jewelry storage system according to claim ~~[[18]]~~ 17, wherein ~~the angle adjusting element is configured~~ jewelry cabinet may be pivoted with respect to the stand to vary the angle α between one of three, four, or five different angles.

20. Canceled

21.(Original) The jewelry storage system according to claim 17, wherein at least one of the plurality of jewelry storage elements is capable of being relocated within the jewelry cabinet.

22.(Currently amended) The jewelry storage system according to claim 17, wherein the plurality of jewelry storage elements includes a bracelet bar and a plurality of shelves attached to one of an interior surface of the ~~box~~ frame and the door.

23.(Original) The jewelry storage system according to claim 22, wherein the bracelet bar is removably attached to the interior surface of the door, the bracelet bar being configured such that it can be moved and relocated to other locations on the interior surface of the door.

24.(Original) The jewelry storage system according to claim 23, wherein the bracelet bar is removably attached to the interior surface of the door by at least one magnet.

25.(Original) The jewelry storage system according to claim 22, wherein the plurality of shelves include at least one front wall member, the front wall member extending upward from a front surface of the shelves.

26.(Original) The jewelry storage system according to claim 25, wherein the plurality of shelves further include movable dividers that divide a top surface of the shelves.

27.(Currently amended) The jewelry storage system according to claim 17, wherein the plurality of jewelry storage elements include a plurality of structures for hanging necklaces attached to at least one of an interior surface of the door and the ~~box~~ frame.

28.(Original) The jewelry storage system according to claim 27, wherein the plurality of jewelry storage elements further include a pouch, wherein the pouch is located beneath the hook bar and is configured to capture lengthy pieces of jewelry placed on the plurality of hooks.

29.(Currently amended) The jewelry storage system according to claim 17, wherein the plurality of jewelry storage elements include an earring bar, the earring bar having a plurality of openings and being attached to at least one of an interior surface of the door and the ~~box~~ frame.

30.(Currently amended) A jewelry storage system for storing and allowing access to and removal of jewelry pieces using at least one movable component, comprising a jewelry cabinet defining an interior space, the jewelry cabinet comprising:

- a ~~box~~ frame including a top wall, bottom wall, two sidewalls and a back wall;

- a door connected to the ~~box~~ frame wherein the door extends substantially from the top wall to the bottom wall;

- at least one vertically extending attachment strip disposed along an interior surface of one of the door and the back wall of the frame; and

- a plurality of jewelry storage elements attached within the interior space, the plurality of jewelry storage elements including at least two different jewelry storage elements selected from a group consisting of a horizontal bracelet bar, an earring bar having a plurality of slits, a hook bar having a plurality of hooks, and a shelf, wherein at least one of the plurality of jewelry storage elements includes a mounting element having a rear side containing at least one attachment device for removable attachment anywhere along a length of the attachment strip ~~is capable of being relocated within the jewelry cabinet.~~

31.(Currently amended) The jewelry storage system according to claim 30, wherein the plurality of jewelry storage elements includes a bracelet bar and a plurality of shelves attached to one of an interior surface of the ~~box~~ frame and the door.

32.(Original) The jewelry storage system according to claim 31, wherein the bracelet bar is removably attached to the interior surface of the door, the bracelet bar being configured such that it can be moved and relocated to other locations on the interior surface of the door.

33.(Original) The jewelry storage system according to claim 32, wherein the bracelet bar is removably attached to the interior surface of the door by at least one magnet.

34.(Original) The jewelry storage system according to claim 31, wherein the plurality of shelves include at least one front wall member, the front wall member extending upward from a front surface of the shelves.

35.(Original) The jewelry storage system according to claim 34, wherein the plurality of shelves further include movable dividers that divide a top surface of the shelves.

36.(Currently amended) The jewelry storage system according to claim 30, wherein the plurality of jewelry storage elements include a hook bar, the hook bar having a plurality of hooks and being removably attached to at least one of an interior surface of the door and the ~~box~~ frame.

37.(Original) The jewelry storage system according to claim 36, wherein the plurality of jewelry storage elements further include a pouch, wherein the pouch is located beneath the hook bar and is configured to capture lengthy pieces of jewelry placed on the plurality of hooks.

38.(Currently amended) The jewelry storage system according to claim 30, wherein the plurality of jewelry storage elements include an earring bar, the earring bar having a plurality of slits and being removably attached to at least one of an interior surface of the door and the ~~box~~ frame.

39.(Original) The jewelry storage system according to claim 30, further comprising:

- a stand configured to receive the jewelry cabinet so that the back wall of the jewelry cabinet forms an angle α from the horizontal;
- a mirror attached to an exterior surface of the door; and
- an angle adjusting element,

wherein the jewelry cabinet may be pivoted with respect to the stand to move between a first position useful for accessing the interior space where the angle α is about 90 degrees and a second position useful for using the mirror where the angle α is less than 90 degrees, the angle adjusting element being configured to determine the angle α .

40.(Original) The jewelry storage system according to claim 39, wherein the angle adjusting element is configured to vary the angle α between one of three, four, or five different angles.

41.(Original) The jewelry storage system according to claim 40, wherein the angle adjusting element is a peg and opening system configured so that when the peg is placed into an opening in one of the jewelry cabinet or stand, the peg holds the jewelry cabinet at the angle α .

42.(Currently Amended) A jewelry storage system for storing and allowing access to and removal of jewelry pieces, comprising a jewelry cabinet defining an interior space, the jewelry cabinet comprising:

- a ~~box~~ frame including a top wall, bottom wall, two sidewalls and a back wall;
- a door connected to the ~~box~~ frame wherein the door extends substantially from the top wall to the bottom wall; and
- a plurality of jewelry storage elements attached within the interior space, the plurality of jewelry storage elements including a ~~horizontal~~ bracelet bar permanently attached to an interior surface of one of the back wall of the ~~box~~ frame and the door, the bracelet bar being attached to one of an interior surface of the box frame and door via a mounting element, the bracelet bar including a first pole having a first free end and extending from a first side of the mounting element to the first free end, and a second pole having a second free end and extending from a second side of the mounting element to the second free end, the first and second poles extending approximately parallel to the interior surface and in close proximity thereto ~~mounting element being configured such that access to at least one end of the bracelet bar is unobstructed by the mounting element.~~

43. Canceled

44. (Currently amended) The jewelry storage system according to claim 42, wherein the plurality of jewelry storage elements includes a plurality of shelves attached to one of the ~~box~~ frame and the door.

45.-46. Canceled

47.(Original) The jewelry storage system according to claim 44, wherein the plurality of shelves include at least one front wall member, the front wall member extending upward from a front surface of the shelves.

48.(Original) The jewelry storage system according to claim 47, wherein the plurality of shelves further include movable dividers that divide a top surface of the shelves.

49.(Currently amended) The jewelry storage system according to claim 42, wherein the plurality of jewelry storage elements include a hook bar, the hook bar having a plurality of hooks and being ~~removably~~ attached to at least one of the interior surface of the door and the ~~box~~ frame.

50.(Original) The jewelry storage system according to claim 49, wherein the plurality of jewelry storage elements further include a pouch, wherein the pouch is located beneath the hook bar and is configured to capture lengthy pieces of jewelry placed on the plurality of hooks.

51.(Currently amended) The jewelry storage system according to claim 42, wherein the plurality of jewelry storage elements include an earring bar, the earring bar having a plurality of slits and being attached to at least one of the interior surface of the door and the ~~box~~ frame.

52.(Withdrawn) A jewelry storage system for storing and allowing access to and removal of jewelry pieces in a wall-mounted or free-standing format, comprising:

a jewelry cabinet defining an interior space, the jewelry cabinet comprising:

a box frame including a top wall, bottom wall, two sidewalls and a back wall;

a door connected to the box frame;

a plurality of jewelry storage elements attached within the interior space; and

a mounting structure on an outer side of the back wall of the box frame configured to permit hanging the jewelry cabinet on a vertical surface; and

a stand for receiving the jewelry cabinet, wherein the jewelry cabinet is configured to be received by the vertical stand so that the back wall of the jewelry cabinet forms an angle of about 90 degrees from the horizontal.

53.(Withdrawn) The jewelry storage system according to claim 52, further comprising a mirror attached to an exterior surface of the door.

54.(Withdrawn) The jewelry storage system according to claim 53, further comprising an angle adjusting element, the angle adjusting element configured to determine the angle a of the jewelry cabinet, with the angle a being between about 60 and 90 degrees.

55.(Withdrawn) The jewelry storage system according to claim 54, wherein the angle adjusting element is configured to vary the angle a between one of three, four, or five different angles.

56.(Withdrawn) The jewelry storage system according to claim 55, wherein the angle adjusting element is a peg and opening system configured so that when the peg is placed into an opening in one of the jewelry cabinet or stand, the peg holds the jewelry cabinet at the angle a .

57. (Currently amended) A jewelry storage system for storing and allowing access to and removal of jewelry pieces, comprising a jewelry cabinet defining an interior space, the jewelry cabinet comprising:

a box frame including a top wall, bottom wall, two sidewalls and a back wall;

a door connected to the box frame wherein the door extends substantially from the top wall to the bottom wall; and

a plurality of jewelry storage elements attached within the interior space, the plurality of jewelry storage elements comprising a horizontal bracelet bar and ~~at least one shelf~~ a plurality of earring bars;

wherein the bracelet bar is permanently attached to an interior surface of one of the back wall and the door via a mounting element;

the bracelet bar includes a first pole having a first free end and extending from a first side of

the mounting element to the first free end, and a second pole having a second free end and extending from a second side of the mounting element to the second free end, the first and second poles approximately parallel to the interior surface of the door and in close proximity thereto;

the plurality of earring bars are permanently attached to the interior surface, above the bracelet bar, via a first vertical element and a second vertical element, each of the plurality of earring bars extending between the first vertical element and the second vertical elements;
and

each of the plurality of earring bars includes a plurality of slits disposed between the first and second vertical elements.

58. (Currently amended) The jewelry storage system according to claim 57, wherein the plurality of jewelry storage elements further comprises at least one shelf, and the at least one shelf ~~include~~ includes at least one front wall member, the front wall member extending upward from a front surface of the shelves.

59. (Currently amended) The jewelry storage system according to claim 57, wherein the plurality of jewelry storage elements further ~~include~~ comprises a hook bar, the hook bar being attached to the interior surface of the door below the bracelet bar and including ~~having~~ a plurality of hooks.

60. (Original) The jewelry storage system according to claim 59, wherein the plurality of jewelry storage elements further include a pouch, wherein the pouch is located beneath the hook bar and is configured to capture lengthy pieces of jewelry placed on the plurality of hooks.

61. Canceled

62. (Currently amended) The jewelry storage system according to claim 57, further comprising:
a stand configured to receive the jewelry cabinet so that the back wall of the jewelry cabinet

forms an angle a from the horizontal; and
an angle adjusting element,
wherein the jewelry cabinet may be pivoted with respect to the stand to move between a first position ~~useful for accessing the interior space~~ where the angle a is about 90 degrees and a second position ~~useful for using the mirror~~ where the angle a is less than 90 degrees, the angle adjusting element being configured to determine the angle a .

63.(Currently amended) A jewelry storage system for storing and allowing access to and removal of jewelry pieces, comprising:

- (a) a jewelry cabinet defining an interior space, the jewelry cabinet comprising:
 - (i) a frame including a top, a bottom, two ~~side~~ sides and a back wall;
 - (ii) a door connected to the ~~box~~ frame wherein the door extends substantially from the top to the bottom;
 - (iii) a plurality of jewelry storage elements attached within the interior space, wherein the jewelry storage elements include a ring storage element bordered by the two sides of the frame ~~plurality of shelves~~, an earring bar comprising a plurality of openings for receiving earrings, and a plurality of structures for hanging necklaces;
 - (iv) wherein ~~at least two jewelry storage elements~~ the earring bar and the plurality of structures for hanging necklaces are attached to an interior surface of the door; and
- (b) a stand configured to receive the jewelry cabinet to hold the jewelry cabinet in an upright position so that the back wall of the jewelry cabinet forms an angle a from the horizontal.

64.(Currently amended) The jewelry storage system according to claim 63, wherein the jewelry cabinet further comprises a shelf including ~~plurality of shelves include~~ at least one front wall member, the front wall member extending upward from a front surface of the shelf ~~shelves~~.

65.(Currently amended) The jewelry storage system according to claim 64, wherein the shelf ~~plurality of shelves~~ further ~~include~~ includes movable dividers that divide a top surface of the ~~shelves~~ shelf.

66.(Previously presented) The jewelry storage system according to claim 63, further comprising a mirror attached to an exterior surface of the door.

67.(Previously presented) The jewelry storage system according to claim 66, further comprising an angle adjusting element, the angle adjusting element configured to determine the angle α of the jewelry cabinet, with the angle α being between about 60 and 90 degrees.

68.(Previously presented) The jewelry storage system according to claim 63, wherein the plurality of jewelry storage elements includes a bracelet bar

69.(Currently amended) A jewelry storage system for storing and allowing access to and removal of jewelry pieces, comprising:

- (a) a jewelry cabinet defining an interior space, the jewelry cabinet comprising:
 - (i) a frame including a top, a bottom, two side sides and a back wall;
 - (ii) a door connected to the frame wherein the door extends substantially from the top to the bottom wall; and
 - (iii) a plurality of shelves a ring storage element attached within the interior space, bordered by the two sides of the frame,
 - ~~(iii) — a plurality of earring bars attached within the interior space, each earring bar comprising a plurality of slits for receiving earrings; and~~
 - ~~(iv) — a plurality of structures attached to the bar for hanging necklaces; and~~
- (b) a stand configured to receive the jewelry cabinet to hold the jewelry cabinet in an upright position so that the back wall of the jewelry cabinet forms an angle α from the horizontal.

70.(Currently amended) The jewelry storage system according to claim 69, wherein the jewelry cabinet further comprises a plurality of shelves, at least one of the plurality of shelves including ~~include~~ at least one front wall member, the front wall member extending upward from a front surface of the at least one shelf ~~shelves~~.

71.(Currently amended) The jewelry storage system according to claim 70, wherein at least one of the plurality of shelves further include ~~includes~~ movable dividers that divide a top surface of the at least one shelf ~~shelves~~.

72.(Previously presented) The jewelry storage system according to claim 69, further comprising a mirror attached to an exterior surface of the door.

73.(Currently amended) The jewelry storage system according to claim ~~[[72]]~~ 69, further comprising an angle adjusting element, the angle adjusting element configured to determine the angle a of the jewelry cabinet, with the angle a being between about 60 and 90 degrees.

74.(Currently amended) The jewelry storage system according to claim 69, wherein the ~~plurality of jewelry storage elements includes~~ the jewelry cabinet further comprises a bracelet bar.

75.(Currently amended) The jewelry storage system according to claim ~~[[69]]~~ 74, wherein at least ~~two jewelry storage elements are~~ the bracelet bar is attached to an interior surface of the door.

76. (New) The jewelry storage system of claim 17, wherein the plurality of jewelry storage elements includes a bracelet bar attached to an interior surface of one of the back wall of the frame and the door, via a mounting element, the bracelet bar including a first pole having a first free end and extending from a first side of the mounting element to the first free end, and a second pole having a second free end and extending from a second side of the mounting element

to the second free end, the first and second poles extending approximately parallel to the interior surface and in close proximity thereto.

77. (New) The jewelry storage system of claim 76, wherein the bracelet bar is attached to the interior surface of the door.

78. (New) The jewelry storage system of claim 76, wherein the plurality of jewelry storage elements further includes a plurality of earring bars disposed above the bracelet bar and attached to the interior surface via a first vertical element and a second vertical element, each of the plurality of earring bars extending between the first vertical element and the second vertical elements, and each of the plurality of earring bars including a plurality of slits disposed between the first and second vertical elements.

79. (New) The jewelry storage system of claim 76, wherein the plurality of jewelry storage elements further includes a plurality of hooks attached to the interior surface, being disposed below the bracelet bar.

80. (New) The jewelry storage system of claim 42, wherein the bracelet bar is attached to the interior surface of the door.

81. (New) The jewelry storage system of claim 80, wherein the plurality of jewelry storage elements further includes a plurality of earring bars disposed above the bracelet bar and attached to the interior surface of the door via a first vertical element and a second vertical element, each of the plurality of earring bars extending between the first vertical element and the second vertical elements, and each of the plurality of earring bars including a plurality of slits disposed between the first and second vertical elements.

82. (New) The jewelry storage system of claim 80, wherein the plurality of jewelry storage elements further includes a plurality of hooks attached to the interior surface of the door, being disposed below the bracelet bar.

83. (New) A jewelry storage system for storing and allowing access to and removal of jewelry pieces, comprising:

- a frame defining an interior space and including a first side, a second side, a top wall extending between the first and second sides, a bottom wall opposing the top wall and extending between the first and second sides, and a back wall extending between the first and second sides and the top and bottom walls;

- a door coupled to the frame;

- a bracelet bar permanently attached to an interior surface of the door via a mounting element, the bracelet bar including a first pole having a first free end and extending from a first side of the mounting element to the first free end, and a second pole having a second free end and extending from a second side of the mounting element to the second free end, the first and second poles extending approximately parallel to the interior surface and in close proximity thereto;

- a plurality of earring bars disposed above the bracelet bar and attached to the interior surface of the door via a first vertical element and a second vertical element, each of the plurality of earring bars extending between the first vertical element and the second vertical element, and each of the plurality of earring bars including a plurality of slits disposed between the first and second vertical elements; and

- a plurality of hooks attached to the interior surface of the door disposed below the bracelet bar.

84. (New) The jewelry storage system of claim 83, further comprising a stand configured to receive the jewelry cabinet so that the back wall of the jewelry cabinet forms an angle α from the horizontal, wherein the jewelry cabinet may be pivoted with respect to the stand to move between a first position useful for accessing the interior space where the angle α is about 90

degrees and a second position useful for using the mirror where the angle α is less than 90 degrees.

85. (New) The jewelry storage system of claim 69, wherein the jewelry cabinet further comprises a bracelet bar attached to an interior surface of one of the back wall of the frame and the door, via a mounting element, the bracelet bar including a first pole having a first free end and extending from a first side of the mounting element to the first free end, and a second pole having a second free end and extending from a second side of the mounting element to the second free end, the first and second poles extending approximately parallel to the interior surface and in close proximity thereto.

86. (New) The jewelry storage system of claim 85, wherein the bracelet bar is attached to the interior surface of the door.

87. (New) The jewelry storage system of claim 63 wherein the ring storage element comprises a plurality of slits for receiving rings.

88. (New) The jewelry storage system of claim 69 wherein the ring storage element comprises a plurality of slits for receiving rings.

89. (New) The jewelry storage system of claim 1 wherein at least a portion of the interior space of the jewelry cabinet is lined with antitarnish cloth.

90. (New) The jewelry storage system of claim 17 wherein at least a portion of the interior space of the jewelry cabinet is lined with antitarnish cloth.

91. (New) The jewelry storage system of claim 30 wherein at least a portion of the interior space of the jewelry cabinet is lined with antitarnish cloth.

92. (New) The jewelry storage system of claim 42 wherein at least a portion of the interior space of the jewelry cabinet is lined with antitarnish cloth.

93. (New) The jewelry storage system of claim 57 wherein at least a portion of the interior space of the jewelry cabinet is lined with antitarnish cloth.

94. (New) The jewelry storage system of claim 63 wherein at least a portion of the interior space of the jewelry cabinet is lined with antitarnish cloth.

95. (New) The jewelry storage system of claim 69 wherein at least a portion of the interior space of the jewelry cabinet is lined with antitarnish cloth.

96. The jewelry storage system of claim 83 wherein at least a portion of the interior space of the frame is lined with antitarnish cloth.

97. (New) A jewelry storage system for storing and allowing access to and removal of jewelry pieces, comprising:

- a frame defining an interior space and including a first side, a second side, a topwall extending between the first and second sides, a bottom wall opposing the topwall and extending between the first and second sides, and a back wall extending between the first and second sides and the top and bottom walls;

- a door coupled to the frame;

- a plurality of earring bars attached to an interior surface of the door via a first vertical element and a second vertical element, each of the plurality of earring bars extending between the first vertical element and the second vertical element, and each of the plurality of earring bars including a plurality of slits disposed between the first and second vertical elements; and

- a plurality of hooks attached to the interior surface of the door disposed below the plurality of earring bars.